

INDUSTRIAL WELDING MACHINES


The background of the entire page is a dark, industrial scene. On the left, a welder's helmet is visible, partially obscured by the text. The right side of the image is filled with numerous bright, orange-yellow sparks that appear to be flying from a welding point, creating a sense of intense heat and activity. The overall color palette is dominated by dark blues and blacks, with the bright sparks providing a high-contrast visual element.

Table of Content

SMAW

52

Inverter Stick Welder

55

MIG Welder

57

Multi-Process Welders

60

TIG Welders

62

Plasma Cutters

63

Diesel Engine Driven Welding Equipment

64

Wire Feeder Welding Equipment

68

Accessories

69

Replacement Parts

70

INDUSTRIAL WELDERS

SMAW

MI 225

PN# 3620



Weight: 61 lbs

Dimensions:

H: 9"

W: 12"

L: 15"



Light Duty

Includes: Power cord, welding cables with electrode holder, ground clamp cable.

Feed	Max Output	Current Range
127 Volts. 39 Amps. Single phase, 60 Hz.	100 Amps. @ 24 Volts. AC, 20% Duty Cycle.	Low 45 to 160 Amps. AC High 85 to 230 Amps. AC
220 Volts. 45 Amps. Single phase, 60 Hz.	155 Amps. @ 25 Volts. AC, 20% Duty Cycle.	

Process

(SMAW) -Flux Coated Electrode AC- Diameter: 1.6, 2.4, 3.2 and 4.0 mm. (1/16", 3/32", 1/8" and 5/32").

TH 200

PN# 3048



Weight: 61 lbs

Dimensions:

H: 11"

W: 8"

L: 16"



Light Duty

Includes: Heavy Duty 3x8 wire feeder cable.1.8 m long.
Clips set for PAS 200 cable holder and welding electrodes housing hooks.

Feed	Max Output	Current Range
127 Volts. 51 Amps. Single phase, 60 Hz	100 Amps. @ 22 Volts.AC 40% Duty Cycle.	50 to 100 Amps. AC
220 Volts. 44 Amps. Single phase, 60 Hz	180 Amps. @ 24 Volts.AC 10% Duty Cycle.	50 to 180 Amps. AC

Process

(SMAW) Flux Coated Electrode - AC- Diameter: 1/16", 1/8" & 5/32"
(1.6 mm to 4.0 mm) E-6011 and E-6013.

CODE 255

PN# 30171



Weight: 57 lbs

Dimensions:

H: 9"

W: 8.7"

L: 16.4 "



Light Duty

Includes: Ground Cable with clip and electrode cable.

Feed	Max Output	Current Range
110 Volts. 60 Amps. Single phase, 60 Hz	125 Amps. @ 23 Volts.AC 20% Duty Cycle.	70 to 125 Amps. AC
220 Volts. 52Amps. Single phase, 60 Hz	200 Amps. @ 26 Volts.AC 10% Duty Cycle.	100 to 230 Amps. AC

Process

(SMAW) Flux Coated Electrode - AC- Diameter: 3/32" (2.4 mm) to 3/16"
(4.8 mm) E-6011 and E-6013.

TH250

PN# 3033



Weight: 92 lbs

Dimensions:

H: 19"

W: 12.5"

L: 13.7"



Light Duty

Includes: Power cord, welding cables with electrode holder, cable holder and welding electrodes housing hooks.

Feed	Max Output	Current Range
127 Volts. 39 Amps. Single phase, 60 Hz.	100 Amps. @ 24 Volts. AC, 30% Duty Cycle.	30 to 100 Amps. AC
220 Volts. 65 Amps. Single phase, 60 Hz	225 Amps. @ 25 Volts. AC, 20% Duty Cycle.	30 to 225 Amps. AC

Process

(SMAW) Flux Coated Electrode - AC- Diameter: 3/32", 1/8" & 5/32"
(2.3 mm to 4.0 mm) E-6011 and E-6013.

TH300

PN# 3389



Weight: 109 lbs
Dimensions:
H: 19"
W: 12.5"
L: 13.7"



Medium Duty

Feed	Max Output	Current Range
127 Volts. 58 Amps. Single fase, 60 Hz.	100 Amps. @ 22 Volts. CA, 30% Duty Cycle.	30 to 100 Amps. AC
220 Volts. 70 Amps. Single fase, 60Hz	270 Amps. @ 28.8 Volts. CA, 20% Duty Cycle.	Low 35 to 200 Amps. AC High 55 to 300 Amps. AC
Process (SMAW) Flux Coated Electrode - AC.- Diameter: 3/32" (2.3 mm), 1/8" (3.2 mm) and 5/32" (4.0 mm).		

TH235/160

PN# 3676



Weight: 112 lbs
Dimensions:
H: 19"
W: 12.5"
L: 13.7"



Medium Duty

Feed	Max Output	Current Range
127 Volts. 39 Amps. Single fase, 60 Hz.	100 Amps. @ 22 Volts. AC/DC, 30% Duty Cycle.	35 to 100 Amps. AC
220 Volts. 58 Amps. Single fase, 60Hz	230 Amps. @ 27 Volts. AC, 150 Amps @ 24 Volts CD 20% Duty Cycle	Low 30 to 190 Amps. AC High 35 to 250 Amps. AC 20 to 160 Amps. DC
Process (SMAW) Flux Coated Electrode - AC & DC.- Diameter: 3/32" (2.3 mm), 1/8" (3.2 mm) and 5/32" (4.0 mm).		

TH320 AC/DC

PN#. 3034



Weight: 139 lbs
Dimensions:
H: 19"
W: 12.5"
L: 13.7"



Medium Duty

Includes: Power cord, welding cables with electrode holder

Feed	Max Output	Current Range
127 Volts. 39 Amps. Single fase, 60 Hz.	100 Amps. @ 24 Volts. AC/DC, 30% Duty Cycle.	35 to 100 Amps. AC 30 to 100 Amps. DC
220 Volts. 70 Amps. Single fase, 60Hz	300 Amps. @ 32Volts. AC, 200 Amps @ 25 Volts CD 20% Duty Cycle	Low 35 to 200 Amps. AC High 55 to 300 Amps. AC 30 to 200 Amps. DC
Process (SMAW) Flux Coated Electrode - AC & DC.- Diameter: 1.6, 2.4, 3.2 and 4.0 mm. (1/16", 3/32", 1/8" and 5/32").		

MI 265 L AC/DC

PN# 3653



Weight: 299 lbs
Dimensions:
H: 21"
W: 19"
L: 27.7"



Medium Duty

Feed	Max Output	Current Range
220 Volts. 84Amps. Single fase, 60 Hz.	250 Amps. @ 30 Volts. AC/DC, 30% Duty Cycle.	Low 25 to 150 Amps. AC High 50 to 275Amps. AC High 45 to 250 Amps. AC Low 20 to 150 Amps. DC
Process (SMAW) Flux Coated Electrode - AC & DC.- Diameter: /16" (1.6 mm) to 1/4" (6.3 mm) TIG (GTAW) Welding wire DC Stainless Steel, Nickel and Copper Alloys. (GTAW) for DC/AC high frequency (optional) DC for Aluminum solder.		

INDUSTRIAL WELDERS

SMAW

MI 2-350 AC/DC

PN# 3632



Weight: 304 lbs
Dimensions:
H: 21"
W: 19"
L: 27.7



Industrail

Feed	Max Output	Current Range
220/440 Volts. 84/42 Amps. Single fase, 60 Hz	250 Amps. @ 30 Volts. AC/DC 50% Duty Cycle.	Low 30 to 150 Amps. AC High 90 to 300 Amps. AC Low 85 to 300 Amps. DC High 25 to 150 Amps. DC

Process

(SMAW) Flux Coated Electrode AC/DC Diámetro: 1/16" (1.6 mm) to 1/4" 6.3 mm).
TIG (GTAW) Welding wire DC Stainless Steel, Nickel and Copper Alloys
AC/DC for Aluminum solder.

MI 265 L DC

PN# 3630



Weight: 304 lbs
Dimensions:
H: 21"
W: 19"
L: 27.7



Industrail

Feed	Max Output	Current Range
220 Volts. 84 Amps. Single fase, 60 Hz	250 Amps. @ 30 Volts. DC 30% Duty Cycle.	Low 25 to 150 Amps. DC High 45 to 250 Amps. DC

Process

(SMAW) Flux Coated Electrode AC/DC Diámetro: 1/16" (1.6 mm) to 3/16" (4.8 mm).
TIG (GTAW) Welding wire DC for 1/8" (3.2 mm)

MI 2-300 DC

PN# 3661



Weight: 286 lbs
Dimensions:
H: 21"
W: 19"
L: 27.7



Industrail

Feed	Max Output	Current Range
220/440 Volts. 83/41.5 Amps. Single fase, 60 Hz	250 Amps. @ 30 Volts. DC 50% Duty Cycle.	Low 25 to 150 Amps. AC High 35 to 300 Amps. DC

Process

(SMAW) Flux Coated Electrode AC/DC Diámetro: 1/16" (1.6 mm) to 1/4" (6.3 mm).
TIG (GTAW) Welding wire DC.

MI 3-400M

PN# 3638



Weight: 299 lbs
Dimensions:
H: 30"
W: 19"
L: 28



Heavy Duty Industrail

Feed	Max Output	Current Range
220/440 Volts. 54/27 Amps. Single fase, 60 Hz	300 Amps. @ 32 Volts. DC 60% Duty Cycle.	60 to 450 Amps. DC

Process

(SMAW) Flux Coated Electrode AC/DC Diámetro: 1/16" (1.6 mm) to 1/4" (6.3 mm).
TIG (GTAW) Welding wire DC.

MI 3-500M

PN# 3639



Weight: 430 lbs

Dimensions:

H: 29.5"

W: 22"

L: 35"



Heavy Duty Industrial

Feed	Max Output	Current Range
220/440 Volts. 80/40 Amps. Tri- phase, 60 Hz	400 Amps. @ 36 Volts. DC 60% Duty Cycle.	70 to 500 Amps. DC
Process		
(SMAW) Flux Coated Electrode DC Diameter: 3/32" (2.3 mm) to 1/4" (6.0 mm). TIG (GTAW) Welding wire DC.		

MI 3-600M

PN# 3644



Weight: 451 lbs

Dimensions:

H: 29.5"

W: 22"

L: 35"



Heavy Duty Industrial

Feed	Max Output	Current Range
220/440 Volts. 110/55 Amps. Tri- phase, 60 Hz	500 Amps. @ 40 Volts. DC 60% Duty Cycle.	80 to 600 Amps. DC
Process		
(SMAW) Flux Coated Electrode DC Diameter: 3/32" (2.3 mm) to 1/4" (6.0 mm). TIG (GTAW) Welding wire DC.		

SRH 444 Golden ARC

PN# 3654



Weight: 299 lbs

Dimensions:

H: 21"

W: 19"

L: 27.7"



Heavy Duty Industrial

Feed	Max Output	Current Range
220/440 Volts. 92/46 Amps. Tri- phase, 60 Hz.	400 Amps. @ 36Volts. AC/DC, 60% Duty Cycle.	Low 60 to 345 Amps. DC High 80 to 550 Amps. DC
Process		
(SMAW) Flux Coated Electrode - DC- Diameter: 1/16" (1.6 mm) to 1/4" (6.3 mm). Especially designed for buildup from 3/32" to 1/4" to and soft type for joining, hard for coating or cutting (cut-weld) Cutting and gouging with carbon electrode and air jet (CAC-A) up to an electrode diameter of 9.5 mm (3/8"). TIG (GTAW) Welding sold with and without high frequency Arc starter.		

ARCTRON 130

PN#1300075



Weight: 6 lbs

Dimensions:

H: 7"

W: 4.3"

L: 12"



INVERTER
TECHNOLOGY

Light Duty

Includes: Power cord, welding cables with electrode holder, ground clamp cable.

Feed	Max Output	Current Range
127 Volts. 34 Amps. Single fase, 50/60 Hz.	110 Amps. @ 22.4 Volts. 20% Duty Cycle.	20 to 130 Amps.
127 Volts. 32 Amps. Single fase, 50/60Hz	110 Amps. @ 14.4 Volts. 20% Duty Cycle.	20 to 130 Amps.
Process		
(SMAW) Flux Coated Electrode Diameter: 1.6 mm to 3.2 mm (1/16" to 1/8") E6010, E6011, E6013, E7018 and E308L. TIG (GTAW) Welding wire Stainless Steel, with "CONTACT-TIG" Tungsten Electrode Diameter: 1 mm to 1.6 mm (0.040" to 1/16").		

INDUSTRIAL WELDERS

Inverter Stick Welders

ARCTRON 160

PN# 3539



Weight: 12.7 lbs

Dimensions:

H: 12.7"

W: 5.5"

L: 14"



INVERTER
TECHNOLOGY

Light Duty

Includes: Power cord, dinse connectors, ground clamp, electrode holder, shoulder strap, welding cables (2 AWG gauge).

Feed	Max Output	Current Range
127 Volts. 36.6 Amps. Single fase, 60 Hz.	120 Amps. @ 25 Volts. 40% Duty Cycle.	20 to 120 Amps.
220 Volts. 38.5 Amps. Single fase, 60Hz	160 Amps. @ 24.4 Volts. 40% Duty Cycle.	

Process

(SMAW) Flux Coated Electrode Diameter: 1.6 mm (1/16") to 4 mm (5/32").
Light Duty (SMAW) and TIG (GTAW). Can be used with most electrodes.

ARCTRON 200

PN# 330142



Weight: 15.4 lbs

Dimensions:

H: 11.6"

W: 6"

L: 16"



INVERTER
TECHNOLOGY

Light Duty

Includes: Power cord, dinse connectors, ground clamp, electrode holder, shoulder strap, welding cables (2 AWG gauge).

Feed	Max Output	Current Range
127 Volts. 43 Amps. Single fase, 60 Hz.	130 Amps. @ 23 Volts. 40% Duty Cycle.	30 to 130 Amps.
220 Volts. 48 Amps. Single fase, 60Hz	200 Amps. @ 26 Volts. 40% Duty Cycle.	

Process

(SMAW) Flux Coated Electrode Diameter: 1.6 mm (1/16") to 4 mm (5/32").
TIG (GTAW) DC. Tungsten electrodes Diameter: .040" and 1/16"

ARCTRON 250 L DC

PN# 30189



Dimensions:

H: 16.5"

W: 9"

L: 20.8"



INVERTER
TECHNOLOGY

Light Duty

Includes: Welding cables dinse connectors are included, electrode holder and ground clamp.

Feed	Max Output	Current Range
220 Volts. 63Amps. Single fase, 60 Hz.	245 Amps. @ 29.8 Volts. 35% Duty Cycle.	30 to 245 Amps.
440 Volts. 28 Amps. Single fase, 60Hz		

Process

(SMAW) Flux Coated Welding wire Diameter: 1.6 mm to 4.8 mm (1/16" to 3/16")
Can be used with E7018, E6013, E6011 plus Stainless Steel and aluminum electrodes

ARCTRON 305

PN# 3766



Weight: 41 lbs

Dimensions:

H: 14.5"

W: 9.5"

L: 18.5"



INVERTER
TECHNOLOGY

Light Duty

Includes: Welding cables dinse connectors.

Feed	Max Output	Current Range
220 Volts. 60Amps. Single fase, 60 Hz.	300 Amps. @ 32Volts. 35% Duty Cycle. Single fase	20 to 300 Amps DC
220 Volts. 41 Amps. Single fase, 60Hz	300 Amps. @ 32Volts. DC 60% Duty Cycle. Tri fase	

Process

(SMAW) Flux Coated Welding wire Diameter: 1.6 mm to 6.4 mm (1/16" to 1/4")
TIG (GTAW) Welding wire DC and Tungsten Electrode Diameter: .040" and 3/32"



MIG Welders

MM 35
 PN# 3592

Weight: 57 lbs
 Dimensions:
 H: 12"
 W: 9"
 L: 20"

Includes: Ground, clamp and cable, and Gas hose. Welding 10' MIG gun 100 Amps

Feed	Max Output	Current Range
127 Volts. 27 Amps. Single fase, 60 Hz	90 Amps. @19 Volts. DC 20% Duty Cycle.	30 to 110 Amps. DC
Process		
MIG (GMAW) Welding wire with/gas Diámetro: 0.6 to 0.9 mm (0.023" to 0.035"). MIG (FCAW) Welding wire without/gas Diámetro: 0.8 to 0.9 mm (0.030" to 0.035") Compatible with Spools up to 4" (102 mm)		

MM 140
 PN# 3041

Weight: 156 lbs
 Dimensions:
 H: 30"
 W: 12"
 L: 30"

Includes: Ground clamp and cable; Low Cylinder rack and Gas hose. MIG Welding gun is sold separately

Feed	Max Output	Current Range
127 Volts. 29 Amps. Single fase, 60 Hz	100 Amps. @19 Volts. DC 30% Duty Cycle.	40 to 120 Amps. DC
Process		
(GMAW) Welding wire Diámetro: 0.6 to 0.9 mm (0.023" to 0.035"). Compatible with Spools up to 4" , 8" and 12" (102, 203, and 305)		

MM 180
 PN# 3042

Weight: 158 lbs
 Dimensions:
 H: 30"
 W: 12"
 L: 30"

Includes: Ground clamp and cable; Low Cylinder rack and Gas hose. MIG Welding gun is sold separately

Feed	Max Output	Current Range
220 Volts. 18 Amps. Single fase, 60 Hz	130 Amps. @20Volts. DC 30% Duty Cycle.	30 to 170 Amps. DC
Process		
(GMAW) Welding wire Diámetro: 0.6 to 0.9 mm (0.023" to 0.035"). (FCAW) Fluxed welding wire Diámetro: 0.8 mm (0.030") Compatible with Spools up to 4" , 8" and 12" (102, 203, and 305)		

MM 252
 PN# 3590

Weight: 238 lbs
 Dimensions:
 H: 31"
 W: 10"
 L: 38"

Includes: Ground clamp and cable; Low Cylinder rack and Gas hose. MIG Welding gun is sold separately

Feed	Max Output	Current Range
220 Volts. 48 Amps. Single fase, 60 Hz	250 Amps. @ 27 Volts. DC 40% Duty Cycle.	30 to 260 Amps. DC
Process		
(GMAW) Welding wire Diámetro: 0.6 to 1.2 mm (0.023" to 0.045") (FCAW) Fluxed welding wire Diámetro: 0.9 mm to 1.2 mm (0.035" to 0.045") Aluminum Wire Diámetro: 0.9 mm and 1.2 mm. (0.035" & 0.045")		

INDUSTRIAL WELDERS

MIG Welders

MM 261

PN# 3591



Weight: 264 lbs

Dimensions:

H: 31"

W: 14"

L: 38"



Industrial

Includes: Ground clamp and cable; Low Cylinder rack and Gas hose. MIG Welding gun is sold separately

Feed	Max Output	Current Range
220/440 Volts. 52/26 Amps. Single fase, 60 Hz	250 Amps. @27 Volts. DC 60% Duty Cycle.	14 to 142 Volts DC 30 to 250 Amps. DC

Process

(GMAW) Welding wire Diámetro: 0.6 to 1.2 mm (0.023" to 0.045")
Stainless steel 0.6mm to 0.9 mm (0.023" to 0.035") .
(FCAW) Fluxed welding wire Diámetro: 0.8 mm (0.030")
Aluminum wire Diámetro: 0.9 mm (0.035")

MM 300 ES

PN# 3145



Weight: 264 lbs

Dimensions:

H: 31"

W: 14"

L: 38"



Industrial

Includes: Ground clamp and cable. Low Cylinder rack and Gas hose. V Grooved Drive Roll Kit for solid wire 0.035" and 0.045"

Feed	Max Output	Current Range
220/440 Volts. 45/22 Amps. Single fase, 60 Hz	250 Amps. @27 Volts. DC 60% Duty Cycle.	30 to 300 Amps. DC

Process

MIG (GMAW) Welding wire Diámetro: 0.6 to 1.2 mm (0.023" to 0.045")
(FCAW) Fluxed welding wire with or without gas Diámetro: 0.9 up to 1.2 mm (0.035" to 0.045")
MIG (GMAW) Aluminum wire Diámetro: 0.9 mm (0.035" to 0.047")

MM 300 PRO

PN# 30191



Weight: 264 lbs

Dimensions:

H: 31"

W: 14"

L: 41"



Industrial

Includes: Ground clamp and cable. Low Cylinder rack and Gas hose. V Grooved Drive Roll Kit for solid wire 0.035" and 0.045", Carrying Cart.

Feed	Max Output	Current Range
220/440 Volts. 60/30 Amps. Single fase, 60 Hz	250 Amps. @26.5 Volts. DC 60% Duty Cycle.	Maximum open Voltage 37 Volts DC 30 to 280Amps. DC

Process

MIG (GMAW) Welding wire Diámetro: 0.6 to 1.2 mm (0.023" to 0.045")
(FCAW) Fluxed welding wire with or without gas Diámetro: 0.9 to 1.2 mm (0.035" to 0.045")
MIG (GMAW) Aluminum wire Diámetro: 0.9 mm to 1.2mm (0.035" to 3/64")

CP 303

PN# 3008



Weight: 273 lbs

Dimensions:

H: 32"

W: 22"

L: 48.5"



Heavy Duty Industrial

Includes: Low Cylinder rack and connectors. Torch sold separately.

Feed	Max Output	Current Range
220/440 Volts. 36/18Amps. Tri- fase, 60 Hz	300 Amps. @32 Volts. DC 100% Duty Cycle.	13 to 36 Volts DC

Process

Weld up to 1/16" (1.6mm) Thickness on Stainless Steel and Aluminum
Process (GMAW) and Fluxed welding wire (FCAW)

DELTAMIG 300

PN# 3491

Heavy Duty Industrial



Weight: 297 lbs

Dimensions:

H: 30"

W: 21"

L: 30"



Includes: Ground clamp and cable. Low Cylinder rack and Gas hose and carry cart.
V Grooved Drive Roll Kit for solid wire 0.9 and 1.2 mm (0.035" and 0.045")

Feed	Max Output	Current Range
220/440 Volts. 32/16 Amps. Tri - phase, 60 Hz	300 Amps. @30 Volts. DC 60% Duty Cycle 230 Amps. @25 Volts. DC 100% Duty Cycle.	16 to 32 Volts DC

Process

MIG (GMAW) Welding wire Diameter: 0.6 to 1.2 mm (0.023" to 0.045")
(FCAW) Fluxed welding wire with or without gas Diameter: 0.9 up to 1.2 mm (0.035" to 0.045")
MIG (GMAW) Aluminum wire Diameter: 0.9 mm (0.035)

DELTAMIG 355

PN# 3002

Heavy Duty Industrial



Weight: 469.5 lbs

Dimensions:

H: 33"

W: 22"

L: 48.5"



Includes: Low Cylinder rack and connectors.
Torch sold separately

Feed	Max Output	Current Range
220/440 Volts. 54/27 Amps. Tri - phase, 60 Hz	350 Amps. @32 Volts. DC 100% Duty Cycle	10 to 32 Volts DC

Process

Weld up to 1/16" (1.6mm) Thickness on Stainless Steel and Aluminum
Process (GMAW) and Fluxed welding wire (FCAW)

DELTAMIG 455

PN# 3003

Heavy Duty Industrial



Weight: 502 lbs

Dimensions:

H: 33"

W: 22"

L: 48.5"



Includes: Low Cylinder rack and connectors.
Torch sold separately

Feed	Max Output	Current Range
220/440 Volts. 73/36.5 Amps. Tri - phase, 60 Hz	450 Amps. @38 Volts. DC 100% Duty Cycle	10 to 38 Volts DC

Process

Weld up to 1/4" (6.3 mm) Thickness on Stainless Steel and Aluminum
Process (GMAW) and Fluxed welding wire (FCAW)
Cutting/gouging capabilities with carbon based electrodes and air (AAC) pressure up to 8mm (5/16")

DELTAMIG 655

PN# 3004

Heavy Duty Industrial



Weight: 546 lbs

Dimensions:

H: 33"

W: 22"

L: 48.5"



Includes: Low Cylinder rack and connectors.
Torch sold separately

Feed	Max Output	Current Range
220/440 Volts. 117/58.7 Amps. Tri - phase, 60 Hz	650 Amps. @44 Volts. DC 100% Duty Cycle 800 Amps. @44 Volts. DC 60% Duty Cycle	10 to 44 Volts DC

Process

Weld up to 3/32" (2.4 mm) Thickness on Stainless Steel and Aluminum
Process (GMAW) and Fluxed welding wire
(FCAW) Aluminum Wire Diameters: 0.9, 1.3 and 1.6 mm (0.035", 0.052" & 1/16")
Cutting/gouging capabilities with carbon based electrodes and air pressure up to 9.5mm (3/8")

INDUSTRIAL WELDERS

Multi-Process Welders

MULTIARC 452

PN# 3603



Weight: 524 lbs

Dimensions:

H: 32"

W: 22"

L: 44"



Heavy Duty Industrail

Wire feeder, Welding Gun and welding cables sold separately.

Feed	Max Output	Current Range
220 Volts. 84 Amps. Tri - fase, 60 Hz.	450 Amps. @ 36 Volts. 100% Duty Cycle.	20 to 515 Amps. DC (CC) 10 to 38 Volts DC (VC)
440 Volts. 44 Amps. Tri - fase, 60Hz	450 Amps. @ 36Volts. 100% Duty Cycle.	

Process

(SMAW). DC Diameter 1/16" to 1/4". - TIG (GTAW) DC
(GMAW) Welding Wire (0.023" to 5/64") Stainless steel (0.023" to 0.045")
(FCAW) with or without gas (0.035" to 3/32")
Cutting/gouging capabilites with carbon based electrodes and air (AAC) (3/8")

MULTIARC 652

PN# 3608



Weight: 524 lbs

Dimensions:

H: 32"

W: 22"

L: 44"



Heavy Duty Industrail

Wire feeder, Welding Gun and welding cables sold separately.

Feed	Max Output	Current Range
220 Volts. 118 Amps. Tri - fase, 60 Hz.	650 Amps. @ 440 Volts DC. 100% Duty Cycle.	15 to 660 Amps. DC (CC) 10 to 44 Volts DC (VC)
440 Volts. 59Amps. Tri - fase, 60Hz	650 Amps. @ 44 Volts. DC 100% Duty Cycle.	

Process

(SMAW). DC Diameter 1/16" to 1/4". - TIG (GTAW) DC
(GMAW) Welding Wire (0.045" to 3/32") Stainless steel (0.023" to 0.045")
(FCAW) with or without gas (0.035" to 1/8")
Cutting/gouging capabilites with carbon based electrodes and air (AAC) (3/8")

Trilogy 200i

PN# 30143



Weight: 33 lbs

Dimensions:

H: 14.7"

W: 8.2"

L: 19"



Heavy Duty

Includes: Welding 10' MIG gun 200 Amps, gas hose and V grooved Drive Roll Kit 0.023" and 0.035". Welding cables and 50mm Dinse connector electrode holder and ground clamp, Power cord 220VAC.

Feed	Max Output	Current Range
127/220 Volts. 30/35 Amps. Single fase, 60 Hz	185 Amps. @23.3 Volts. DC 35% Duty Cycle.	35 to 210 Amps. DC

Process

(SMAW) Coated Electrode, DC Diámetro: 1.6 mm (1/16") to 3.2 mm (1/8").
TIG (GTAW) Tungsten Electrode, DC Diámetro: 0.40" & 1/16".
MIG (GMAW) and (FCAW) Diámetro: 0.6 mm to 0.9 mm (0.023" to 0.035")

OPUS 2K 355

PN# 3507



Weight: 83 lbs

Dimensions:

H: 17.5"

W: 13.7"

L: 24"



INVERTER
TECHNOLOGY

Heavy Duty

Wire feeder, Welding Gun and welding cables sold separately.

Feed	Max Output	Current Range
220/440 Volts. 50/26 Amps. Single fase, 60 Hz.	225 Amps. @ 29 Volts. DC 60% Duty Cycle.	5 to 400 Amps. DC (CC) 10 to 35 Volts DC (VC)
220/440 Volts. 32/20 Amps. Tri - fase, 60Hz	300 Amps. @ 32Volts. DC 60% Duty Cycle.	

Process

(SMAW) Coated Electrode DC Diameter 1/16" to 1/4".
TIG (GTAW) DC Up to 1/4" (64mm) Thickness
MIG (GMAW) Welding Wire (0.023" to 0.045") Stainless steel (0.030" to 0.045")
MIG (FCAW) with or without gas (0.035" to 1/16")
MIG Aluminum 0.035", 0.052" & 1/16" with wire feeder and gun

OPUS 2K 355 S

PN# 30192



INVERTER
TECHNOLOGY

Weight: 83 lbs
Dimensions:
H: 17.5"
W: 13.7
L: 24"



Heavy Duty

Wire feeder, Welding Gun and welding cables sold separately.

Feed	Max Output	Current Range
220/440 Volts. 32/20 Amps. Single fase, 60 Hz.	225 Amps. @ 29 Volts. DC 60% Duty Cycle.	5 to 400 Amps. DC (CC)
220/440 Volts. 32/20 Amps. Tri - fase, 60Hz	300 Amps. @ 32Volts. DC 60% Duty Cycle.	10 to 35 Volts DC (VC)

Process

(SMAW) STICK Coated Electrode DC Diameter 1/16" to 1/4".
TIG (GTAW) DC Contact- Tig Arc Starter.
MIG (GMAW) Welding Wire 0.9 mm to 1.6 mm (0.035" to 1/16")
MIG (GMAW-P) Diámetro: 0.9 mm to 1.6 mm (0.035" to 1/16")
MIG (FCAW) 0.9 mm up to 1.2 mm (0.035" to 0.045")
Cutting/gouging capabilities with carbon based electrodes and air (CAC-A)

OPUS 560

PN# 30143



INVERTER
TECHNOLOGY

Weight: 120 lbs
Dimensions:
H: 18"
W: 14"
L: 26"



Heavy Duty

Wire feeder, Welding Gun and welding cables sold separately.

Feed	Max Output	Current Range
220/440 Volts. 59/29 Amps. Tri - fase, 60 Hz	450 Amps. @38 Volts. DC 100% Duty Cycle.	5 to 600 Amps DC (CC) 10 to 38 Volts. D (VC)

Process

(SMAW) Coated Electrode, DC Diámetro: (1/16" to 1/4")
TIG (GTAW) DC Up to 1/4" (64mm) Thickness
MIG (GMAW) Diámetro: (0.035" to 1/16") Stainless steel (0.035" to 1/16")
MIG (FCAW) with or without gas (0.035" to 3/32")
MIG Aluminum 0.035", 0.052" & 1/16" with wire feedre and gun
Cutting/gouging capabilities with carbon based electrodes and air (CAC-A) up to 3/8"

OPUS 560 S

PN# 30193



INVERTER
TECHNOLOGY

Weight: 120 lbs
Dimensions:
H: 18"
W: 14"
L: 26"



Heavy Duty

Wire feeder, Welding Gun and welding cables sold separately.

Feed	Max Output	Current Range
220/440 Volts. 59/29 Amps. Tri - fase, 60 Hz	450 Amps. @38 Volts. DC 100% Duty Cycle.	5 to 600 Amps DC (CC) 10 to 38 Volts. D (VC)

Process

(SMAW) STICK Coated Electrode,
TIG (GTAW) DC DC Contact- Tig Arc Starter
MIG (GMAW) Diámetro: (0.035" to 1/16") Stainless steel (0.035" to 1/16")
MIG (FCAW) 0.9 mm up to 2.4 mm (0.035" to 3/32")
MIG (GMAW-P) Diámetro: 0.9 mm up to 1.6 mm (0.035" to 1/16")
Cutting/gouging capabilities with carbon based electrodes and air (CAC-A)

FORTIS MIG 355i

PN# 30194



INVERTER
TECHNOLOGY

Weight: 83 lbs
Dimensions:
H: 17"
W: 13.7"
L: 24"



Heavy Duty

Wire feeder, Welding Gun and welding cables sold separately.

Feed	Max Output	Current Range
220/440 Volts. 32/20 Amps. Tri - fase, 60 Hz	300 Amps. @29 Volts. DC 60% Duty Cycle 225 Amps. @25 Volts. DC 60% Duty Cycle.	10 to 35 Volts. D (VC)

Process

MIG (GMAW) Diámetro: Welding wire 0.9mm to 1.6 mm (0.035" to 1/16")
MIG (GMAW-P) Diámetro: 0.9 mm to 1.6 mm (0.035" to 1/16")
MIG (FCAW) 0.9 mm up to 1.2 mm (0.035" to 0.045")

INDUSTRIAL WELDERS

TIG Welders

ARCTRON 205 HF

PN# 3489



INVERTER
TECHNOLOGY

Light Duty

Weight: 33 lbs

Dimensions:

H: 14.7"

W: 8.2"

L: 19"



Includes: Remote Control RHS-2 for HF starting, welding hose and cables with dinse connector are included. TIG welding torch is sold separately.

Feed	Max Output	Current Range
220 Volts. 45 Amps. Dual fase, 60 Hz	180Amps. @27 Volts. DC 40% Duty Cycle.	20 to 180 Amps DC

Process

(SMAW) Coated Electrode, DC Diámetro: (1/16" to 3/16")
TIG (GTAW) Tungsten Electrode, DC Diámetro: 0.40" to 1/8"
(GTAW-P) DC
2T, 4T BiNivel Trigger and Crater Fill for TIG only

MI 150 AF

PN# 3016



Industrial

Weight: 192 lbs

Dimensions:

H: 25"

W: 12.5"

L: 23.5"



Torch and accessories are sold separately

Feed	Max Output	Current Range
220 /440Volts. 60/30 Amps. Single fase, 60 Hz	150 Amps. @26 Volts. DC 50% Duty Cycle 100 Amps. @24 Volts. DC 100% Duty Cycle.	Low 10 to 80 Amps AC High 30 to 175 Amps AC Low 10 to 150 Amps DC High 20 to 156 Amps DC

Process

(SMAW) Coated Electrode, AC or DC - Diámetro: (1/16" to 1/8")
TIG (GTAW) AC or DC -high frequency starter.
Use Torch with cooling valve.

ARCTRON 285 HF

PN# 3490



INVERTER
TECHNOLOGY

Light Duty

Weight: 83 lbs

Dimensions:

H: 17.5"

W: 13.7

L: 24"



Includes: Remote Control RHS-2 for HF starting, welding hose and cables with dinse connector are included. TIG welding torch is sold separately

Feed	Max Output	Current Range
220 Volts. 52 Amps. Dual fase, 60 Hz.	200 Amps. @ 28 Volts. DC 60% Duty Cycle.	20 to 200 Amps. DC
220 Volts. 41Amps. Tri - fase, 60Hz	280 Amps. @ 31 Volts. DC 40% Duty Cycle.	20 to 285 Amps DC

Process

(SMAW) Coated Electrode, DC Diámetro: (1/16" to 1/4")
TIG (GTAW) Tungsten Electrode, DC Diámetro: 0.40" to 1/8"
(GTAW-P) DC
2T, 4T BiNivel Trigger and Crater Fill for TIG only

MI 2 300 AC DC AF

PN# 3633



Heavy Duty

Weight: 310 lbs

Dimensions:

H: 21"

W: 19"

L: 27.7"



Torch and accessories are sold separately

Feed	Max Output	Current Range
220 /440Volts. 84/42 Amps. Single fase, 60 Hz	150 Amps. @30 Volts. AC DC 50% Duty Cycle 200 Amps. @24 Volts. CA TIG (GTAW) 50% Duty Cycle.	Low 50 to 200 Amps AC High 30 to 300 Amps AC Low 50 to 250 Amps DC High 25 to 300 Amps DC

Process

(SMAW) Coated Electrode, AC or DC - Diámetro: (1/16" to 1/4")
TIG (GTAW) AC or DC -high frequency starter.
Cutting/gouging capabilities with carbon based electrodes and air (CAC-A) up to 3/16"



ALPHA TIG 230 D

PN# 3548



Weight: 343 lbs
Dimensions:
H: 33"
W: 19"
L: 42.7"



Heavy Duty

Includes: Remote Control MFTC14, welding hose and cables with dinse connector and carrying cart.

Feed	Max Output	Current Range
220 Volts. 61.4 Amps. Single fase, 60 Hz	150 Amps. @26 Volts. AC DC 40% Duty Cycle	5 to 230 Amps AC/DC

Process

(SMAW) Coated Electrode, AC or DC - Diámetro: (1/16" to 3/16")
TIG (GTAW) AC or DC -high frequency starter.
(GTAW-P) optional Pulstig 302

ALPHA TIG 352 DP

PN# 3396



Weight: 343 lbs
Dimensions:
H: 33.5"
W: 22"
L: 48.5"



Heavy Duty

Includes: High frequency starter for Arc stability and Remote Control MFTC14

Feed	Max Output	Current Range
220/440 Volts. 123/63 Amps. Single fase, 60 Hz	NEMA Class 1 (70) 350 Amps. @34 Volts. AC DC 50% Duty Cycle	3 to 400 Amps AC/DC

Process

(SMAW) Coated Electrode, AC or DC - Diámetro: (1/16" to 1/4")
TIG (GTAW) AC or DC -High frequency starter for Arc stability
(GTAW-P) Integrated Pulsating Arc
Cutting/gouging capabilites (CAC-A) up to 1/4"

ALPHA TIG 252 DP

PN# 3381



Weight: 418 lbs
Dimensions:
H: 33"
W: 22"
L: 48.5"



Super Heavy Duty

Includes: High frequency starter for Arc stability and Remote Control MFTC14

Feed	Max Output	Current Range
220/440 Volts. 100/50 Amps. Single fase, 60 Hz	NEMA Class 1 (60) 250 Amps. @30 Volts. AC DC 60% Duty Cycle	5 to 310 Amps AC/DC

Process

(SMAW) Coated Electrode, AC or DC - Diámetro: (1/16" to 1/4")
TIG (GTAW) AC or DC -High frequency starter for Arc stability
(GTAW-P) Integrated Pulsating Arc
Cutting/gouging capabilites (CAC-A) up to 3/16"

Plasma Cutters

HOT POINT i45

PN# 3175



Weight: 42 lbs
Dimensions:
H: 13"
W: 8.5"
L: 19"



INVERTER
TECHNOLOGY

Light Duty

Includes: Plasma handheld torch, 20ft. power cord and ground cable and clamp are Start-up kit consumables.

Feed	Cutting	Gouging Depth
220 Volts. 36 Amps. AC Single fase, 60 Hz	1/2" (12.7 mm) Carbon Steel 3/8" (9.5 mm) Aluminum	3.2 mm (1/8")

Process

Plasma cutter is capable of cutting 12.7 mm (1/2") on carbon/steel sheets and 9.5 mm (3/8") aluminum and cutting up to 19 mm (3/4") on base materials.

INDUSTRIAL WELDERS

Plasma Cutters

HOT POINT i65

PN# 3784



Weight: 55 lbs
Dimensions:
H: 15"
W: 9"
L: 19.6"



INVERTER
TECHNOLOGY

Industrial

Includes: Plasma handheld torch, 20ft. power cord and ground cable and clamp are Start-up kit consumables.

Feed	Cutting	Gouging Depth
220 Volts. 36 Amps. AC Tri - fase, 60 Hz	3/4" (19 mm) Carbon Steel 1/2" (12 mm) Aluminum	1/8" (3.2 mm)

Process

Plasma cutter is capable of cutting 19 mm (3/4") on carbon/steel sheets and 12 mm (1/2") aluminum and cutting up to 25.4mm (1") on base materials.

HOT POINT 1500

PN# 3586



Weight: 374 lbs
Dimensions:
H: 44.5"
W: 22.5"
L: 26"



Super Heavy Duty

Includes: Plasma handheld torch, ground clamp, air compressor and water purging automatic outlet.

Feed	Cutting	Gouging Depth
220 /440Volts. 69/34 Amps. AC Tri - fase, 60 Hz	1-1/4" (32 mm) Steel and Stainless steel 1" (25 mm) Aluminum	1/4" (6.4 mm)

Process

Equipment capable of Cutting up to 1-1/2" (38mm) on carbon steel and stainless steel 1-1/4" (32 mm) on aluminum with compressed air.

HOT POINT 1125

PN# 3582



Weight: 55 lbs
Dimensions:
H: 15"
W: 9"
L: 19.6"



Heavy Duty

Includes: Plasma handheld torch, ground clamp, air compressor and water purging automatic outlet.

Feed	Cutting	Gouging Depth
220/440 Volts. 80/40 Amps. AC 1 Phase 60 Hz	1" (25 mm) Steel and Stainless steel 3/4" (19 mm) Aluminum	1/4" (6mm)

Process

Equipment capable of Cutting up to 1" (25mm) on carbon steel and 3/4" (19mm) on aluminum with compressed air.

Gas Generator Welding Equipment

BRONCO 3700 K

PN# 3511



Weight: 231 lbs
Dimensions:
H: 28"
W: 28"
L: 33.8"



Auxiliary Output
4,000
Peak Watts

Medium Duty

Includes: Cart

Max Output	Amperage Welding Range	Power Output
140 Volts. 25 Amps. DC 40% Duty Cycle.	60 to 140 Amps DC	120/220 Volts 31/15.5 Amps Single fase 60 Hz 3700 watts

Process

(SMAW) Coated Electrode DC Diameter 1/16" to 1/8" (1.6 mm to 3.2 mm)
Dual Capabilites as welder and a power generator.

BRONCO 160

PN# 30170



Weight: 231 lbs
Dimensions:
H: 25"
W: 26"
L: 32.5"



Auxiliary Output
6,500
Peak Watts

Medium Duty

Includes: Cart

Max Output	Amperage Welding Range	Power Output
160 Volts. 24.4 Amps. DC 40% Duty Cycle.	15 to 160 Amps DC	120/240 Volts AC Single phase 60 Hz 6200 watts

Process

(SMAW) Coated Electrode DC Diameter 1/16" to 5/32" (1.6 mm to 4.0 mm)
TIG (GTAW) Stainless steel welding wire with "Contact TIG" system and Tungsten Electrode, DC Diameter: 0.040" and 1/16"
Dual Capabilities as welder and a power generator.

BRONCO 320 K XD

PN# 3043



Weight: 742 lbs
Dimensions:
H: 44"
W: 27.7"
L: 46"



Auxiliary Output
11,500
Peak Watts

Industrial

Max Output 100% Duty Cycle	Max Output	Current Range Voltage	Max Voltage	Power Output Single Fase 60 Hz
300 A @ 25 V CC/AC 300 A @ 25 V CC/ DC	300 A @ 25 V 300 A @ 25 V 300 A @ 25 V	50 - 320 A 50 - 320 A 17 - 28 V	80 V, AC 72 V, DC 41 V, VC	11.5 KVA / Kw Pico 10.5 KVA / Kw Con- tinuo 120/240 V, 60 Hz.- Single fase

Process

(SMAW) STICK Coated Electrode, DC Diámetro: (1/16" to 3/16")
TIG (GTAW) DC DC Contact- Tig Arc Starter
MIG (GMAW) Diámetro: (0.030" to 0.045")
MIG (FCAW) Diámetro: (0.030" to 1/16") with S-302T wire Feeder
MIG Aluminum Diámetro: (0.035" to 1/16") with Push/Pull Torch (optiona)
Cutting/gouging capabilities with carbon based electrodes and air (CAC-A) up to 1/4"

BRONCO 255 K XD

PN# 3646



Weight: 593 lbs
Dimensions:
H: 43"
W: 27.7"
L: 44"



Auxiliary Output
11,000
Peak Watts

Industrial

Max Output 100% Duty Cycle	Max Output	Current Range Voltage	Max Voltage	Power Output Single Fase 60 Hz
250A @ 25 V CC/AC 250 A @ 25 V CC/ DC 250A @ 28 V VC/DC	250 A @ 25 V 250 A @ 25 V 250 A @ 25 V	45 - 250 A 45 - 250 A 17 - 28 V	80 V, AC 72 V, DC 41 V, VC	11,000 KVA / Kw Pico 10 KVA / Kw Continuo 120/240 V, 60 Hz.- Single fase

Process

(SMAW) STICK Coated Electrode, DC Diámetro: 1/16" to 3/16")
TIG (GTAW) DC DC Contact- Tig Arc Starter
MIG (GMAW) Diámetro: (0.030" to 0.045")
MIG (FCAW) Diámetro: (0.030" to 1/16") with S-302T wire Feeder
MIG Aluminum Diámetro: (0.035" to 1/16") with Push/Pull Torch (optiona)
Cutting/gouging capabilities with carbon based electrodes and air (CAC-A) up to 3/16"

BRONCO 5500K

PN# 3492



Weight: 436 lbs
Dimensions:
H: 28"
W: 19"
L: 37"



Auxiliary Output
6,500
Peak Watts

Industrial

Includes: Cart

Max Output	Amperage Welding Range	Power Output
25 V-200A DC 20% Duty Cycle. 25 V-150A . DC 100% Duty Cycle.	45 to 200 Amps DC	120/240 Volts 46/23 Amps Single fase 60 Hz 6500 watts

Process

(SMAW) Coated Electrode DC Diameter 1/16" to 5/32" (1.6 mm to 4.0 mm)
Dual Capabilities as welder and a power generator.

INDUSTRIAL WELDERS

Diesel Engine Driven Welding Equipment

GEMINIS 500i CC

PN# 30195

Super Heavy Duty

Weight: 1538.8 lbs

Dimensions:

H: 56"

W: 31.5"

L: 66"



Includes: Remote Control RHS-2 for HF starting, welding hose and cables with dinse connector are included. TIG welding torch is sold separately

Max Output 100% Duty Cycle	Amperage Welding Range	Power Output
500 Amp. @ 28 Volts DC (CC).	20 to 500 Amps	20kW 240 Volts tri fase, 60 Hz (Generator)
230 Amp. @ 28 Volts DC and DC (CC)	10 to 230 Amps double side 10 to 300 Amps single side	4.0 kW, 120/240 Volts single fase (Welding)

Process

(SMAW) Coated Electrode DC Diameter 1.6mm to 6.4mm (1/16" to 1/4") (Cut-Arc)
MIG (FCAW) with or without gas 0.8mm to 1.6 mm (0.030" to 1/16") with S512P Feeder.
TIG (GTAW) DC with high frequency Arc stabilizer
Cutting/gouging capabilities with carbon based electrodes and air (CAC-A) up to 5/16"
Dual Capabilities as welder and a power generator



GEMINIS 600 P CC/CV

PN# 3538

Super Heavy Duty

Weight: 2325 lbs

Dimensions:

H: 74"

W: 34.5"

L: 76.7"



Max Output	Amperage Welding Range	Power Output
550 Amps. @ 30 Volts., DC (CC) 275 Amps. @ 30 Volts., DC (CC) 40% Duty Cycle	10 to 32 Volts., DC (VC)	4.0 Kw 120/240 Volts., Single Fase, 60 Hz

Process

(SMAW) Coated Electrode DC Diameter 1.6mm to 6.4mm (1/16" to 1/4")
TIG (GTAW) DC with high frequency Arc stabilizer
MIG (GTAW) Diameter (0.030" to 0.045")
MIG (FCAW) with or without gas 0.8mm to 2.0 mm (0.030" to 5/64").
Cutting/gouging capabilities with carbon based electrodes and air (CAC-A) up to 3/16"
Dual Capabilities as welder and a power generator



ABACUS 320 KB

PN# 3553

Super Heavy Duty

Weight: 901 lbs

Dimensions:

H: 52.5"

W: 19.5"

L: 50.7"

Auxiliary 4k ouput available

Max Output 100% Duty Cycle	Amperage Welding Range	Power Output
300 Amps. @ 25 Volts., CC/AC	50 to 320 Amps. AC	11,500 Peak watts
300 Amps. @ 25 Volts., CC/DC	50 to 320 Amps. AC	10,500 watts
300 Amps. @ 25 Volts., DC/VC	17 - 28 Volts. DC	

Process

(SMAW) Coated Electrode DC Diameter 1.6 to 6.4 mm (1/16" to 1/4").

TIG (GTAW) DC with high frequency Arc stablizer (optional)

MIG (GTAW) DC with wire feedr S302 (optional)

Cutting/gouging capabilites with carbon based electrodes and air (CAC-A) up to 3/16"



Insignia 504 P CC

Electric Control

PN# 3549

Stock 304-562

Process DC - TIG Electrode

Super Heavy Duty



Auxiliary 4k ouput available

Max Output	Amperage Welding Range	Motor
400 Amps. @ 36 Volts., 100% D.uty Cycle	45 to 500 Amps.	4 CIL., 32.6 HP., Perkins 1800 RPM

Auxiliary 4k ouput available on all models

Insignia 504 P CC/CV

Electric Control

PN# 3550

Stock 304-563

Process DC - TIG/MIG Electrode

Super Heavy Duty



Auxiliary 4k ouput available

Max Output	Amperage Welding Range	Motor
500 Amps. @ 30 Volts., 60% CD/CC	20 to 550 Amps.	4 CIL., 32.6 H.P., Perkins 1800 RPM
400 Amps. @ 36 Volts., 100% CD/VC	14 - 40 Volts.	

Process

(SMAW) Coated Electrode DC Diameter: 1.6mm to 6.4 mm (1/6" to 1/4") (CUT-WELD).

(GMAW) electrode or welding wire Diameter 0.6mm to 1.2 mm (0.023 to 0.045")

(GMAW) Stainless steel Diameter: 0.8mm to 1.2 mm (0.030" to 0.045")

(FCAW) with speed feeder Diameter: 0.8mm to 1.6 mm (0.030" to 1/16").

(FCAW) with voltage sensitive feeder Diameter: 0.8 to 1.6 mm (0.030" to 1/16").

(MIG) aluminum Diameter: 0.8mm to 1.6 mm (0.030" to 1/16").

TIG (GTAW) DC, with high frequency Arc stablizer (optional)

Cutting/gouging capabilites with carbon based electrodes and air (CAC-A) up to 5/16"



INDUSTRIAL WELDERS

Wire Feeder Welding Equipment

Wire Feeder S 302 MT

PN# 3005



Weight: 35 lbs

Dimensions:
H: 15.2"
W: 11"
L: 24"



Power Input	WireThickness	Speed
24 Volts. @ 3.5 Amps. AC Single Fase, 50/60 Hz.	0.6mm to 2.0 mm (0.023" to 5/64")	1.9 to 23 m x min. (75 to 900 Inches. x min.)

Compatible

-DELTAMIG 355, OPUS 560 and 2K 355

Wire Feeder S 302 T

PN# 3085



Weight: 35 lbs

Dimensions:
H: 15.2"
W: 11"
L: 25.2"



Power Input	WireThickness	Speed
24 Volts. @ 3.5 Amps. AC Single Fase, 50/60 Hz.	0.6mm to 2.0 mm (0.023" to 5/64")	1.9 to 23 m x min. (75 to 900 Inches. x min.)

Compatible

-CP 303, DELTAMIG 355, BRONCO 255 K XD and 320 K XD (gas), ABACUS 320 KB and INSIGNIA.

Wire Feeder S 512 P

PN# 3542



Weight: 35 lbs

Dimensions:
H: 17"
W: 8.5"
L: 21.5"



Power Input	WireThickness	Speed
14 - 48 VDC 100 Max. OCV	0.6 mm to 2.0 mm (0.023" to 5/64")	1.52 to 21.6 m x min. (60 to 850 Inches. x min.)

Compatible

MI-3 400, MI-3 500, MI-3 600, SRH-444 and INSIGNIAS type CC

Cooling System EFA 255

PN# 3802



Includes: Hoses and adaptors



Power Input	Connections	Applications
127 Volts, 5.8 Amp., 11600 Btu/hr Single fase and 60 Hz	Connections of 16 mm left rope (5/8" LH) with grape seat, (picha) at the water inlet and outlet	Water chiller system, developed for the cooling of the TIG (GTAW) torch, with a capacity of 5 liters

Wire Feeder S 604 MT

PN# 3010



Weight: 43 lbs

Dimensions:
H: 15.2"
W: 11"
L: 25.2"



Power Input	WireThickness	Speed
24 Volts. @ 4 Amps. AC Single Fase, 50/60 Hz.	0.6mm to 3.2 mm (0.023" to 1/8")	1.9 to 23 m x min. (75 to 900 Inches. x min.)

Compatible

CP 303, DELTAMIG 355, 455 & 655, BRONCO 255 K XD, 320 K XD (gas) & INSIGNIA MULTIARC 452 & 652

Wire Feeder S 604 MT

PN# 30095



Weight: 43 lbs

Dimensions:
H: 15.2"
W: 11"
L: 25.2"



Power Input	WireThickness	Speed
24 Volts. @ 10Amps. AC Single Fase, 50/60 Hz.	0.6mm to 3.2 mm (0.023" to 1/8")	1.3 to 19.8 m x min. (50 to 780 Inches. x min.)

Compatible

CP 303, DELTAMIG 355, 455 & 655, OPUS 560 and 2K 355, MULTIARC 452 and 652

Wire Feeder S 512 P CV

PN# 30148



Weight: 35 lbs

Dimensions:
H: 17"
W: 8.5"
L: 21.5"



Power Input	WireThickness	Speed
24 Volts @ 3.5 Amps AC Single fase 50/60 Hz	0.6 mm to 2.0 mm (0.023" to 5/64")	1.9 to 23 m x min. (75 to 900 Inches. x min.)

Compatible

DELTAMIG 355, OPUS

Carrying Cart for Welding Equipment

PN# 3817






Accessories

Remote Control RFC-14

PN# 3353



Weight: 10.5 lbs

Dimensions:
H: 7.6"
W: 6.2"
L: 10.8"



Description
Remote foot control, to regulate current and start the arc in TIG process machines (ALPHATIG, MULTIARC and OPUS). Includes power cord and terminal plug

HFU UNIT 252

PN#3801



Weight: 15 kg
Dimensions:
H: 12"
W 12"
L: 15"



Power Input	Description
127/220 Volts. 1.1/0.6 A.	Apparent power: 0.144 kVA. Maximum capacity: 300 A AC/DC@100% duty cycle. Complete with: Post-flow control (timer). Power cord with three-pin plug. Connection cables. Start or continuous AF switch. Gas valve. Water valve (optional).

Electrode Holders

250 Amps.

PN# 8330
5-PE-250



300 Amps.

PN# 8320
5-PE-300



500 Amps.

PN# . 8325
5-PE-500



Description
The best electrical conductivity. Insulators molded with thermo setting plastics resistant to flame and rough treatment. New larger handle with thicker walls. Successfully tested under extreme working conditions with amperage higher than recommended. For continuous use with high electrode diameters and current intensity, heavy steelwork, structures, pipes, etc.

250 Amps.

PN# 81100
5M250A
Mundial Brand



300 Amps.

PN# 81101
5M250A
Mundial Brand



Description
High content copper alloy for excellent electrical conductivity Manufactured with fiber glass body for extreme working conditions with amperage higher than recommended. 60% Duty Cycle.

Ground Clips

300 Amps.

PN# 8305
5-PT- 300



500 Amps.

PN# 8315
5-PT- 500




Description
Designed in cast copper-zinc for high conductivity on large, flat contact surfaces. Pressure jaws to always maintain good contact. For continuous heavy duty, for cables 1/0 and 2/0 and 300 and 500 amps. respectively.

Ground Clamps


250 Amps.

PN# . 8280
5-T-250




300 Amps.

PN# 8285
5-T- 300



500 Amps.


PN# 8290
5-T- 500



Description
Design allows pressure jaws to always maintain good contact. Weatherproof tested to work extreme conditioons. Available for 250, 300 and 500 Amps


250 Amps.

PN# 8864
5-T-250-E




300 Amps.

PN# 8865
5-T- 300-E



500 Amps.

PN# 8866
5-T- 500-E



Description
500 Amps new design allows pressure jaws to always maintain good contact. Weatherproof tested to work extreme conditioons. Also available for 250 and 300 Amps.

INDUSTRIAL WELDERS

Welding Cable Connector

300 Amps.

PN# 8295
5-ZAP-300



500 Amps.

PN# 8300
5-ZAP-500

Description

Manufactured in copper-zinc casting with a functional design so that it fits perfectly to the terminals of welding machines. Practical and easy to connect to the ends of the cables for electrode holders or ground clamps, available in 300 and 500 amps, for cables up to 1/0 and 2/0. To be used both in ground clamps or in welding machine terminals.

Cable Connector

1/0 – 2/0

PN# 8599
5-ZAP-300



Description

Manufactured in copper with wide opening for easy to connect to the ends of the cables. Use with the 9/16" terminal.

Welding Terminals

2 Piece Kit

PN# 30112
Compatible with
MM, MI, CP, MULTIARC,
BRONCO and SRH



3 Piece Kit

Cód. 30120*
Compatible
with TH, MI 80,
MI 130 and MI 225 L



Replacement parts for PT-80 Welding Equipment Hot Point i45

PN#	Model	PN#	Model
3775*	Plasma Torch PT-80 6M	3779*	DIFUSOR PT-80
3776	Nozzle PT-80	3780	ELECTRODO PT-80
3777	Nozzle PT-80	3781	TOBERA PT-80 CONTACTO, 1 mm
3778*	Torch Handle PT-80	3782*	TOBERA PT-80, 40-50A, 1 mm

1600157 - Replacement bundle for Hot Point i45

Replacement parts for PT-100 Welding Equipment Hot Point i65

PN#	Model	PN#	Model
3825*	Plasma Torch PT-100 6M	3822*	Electrode
3819*	TOBERA. Diam. 1.0 40-50 A	3823*	Cooling Tube System
3820*	Nozzle 30-70 A	3818*	Difuser Ring 30-70 A
3821*	Drag Splitter		

1600159 - Replacement bundle for Hot Point i65

Replacement parts Trilogy 200i Torch

PN# 1600158 - Dual Package for Trilogy 200i 0.035" and 0.045"

Accessories

PN#	Description
1600164	Socket 35-50 for Arctron 160 and 200 Machines 
1600165	Socket speed connector 35-50 for INFRA Machines 
1600166	Micro wire feeding spool Diametres 0.035" and 0.045" 